



# Acoustical Surfaces, Inc.

SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318

(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: [sales@acousticalsurfaces.com](mailto:sales@acousticalsurfaces.com)

Visit our Website: [www.acousticalsurfaces.com](http://www.acousticalsurfaces.com)

---

---

**We Identify and S.T.O.P. Your Noise Problems**

7/22/15

We certify that UltraTouch™ Denim Insulation, UltraTouch™ Radiant Barrier, and Echo Eliminator Acoustic Panels do not contain any of the following chemicals and conforms to the LBC Imperative 11 – Red List.

- Alkylphenols
- Asbestos
- Bisphenol A (BPA)
- Cadmium
- Chlorinated Polyethylene and Chlorosulfonated Polyethylene
- Chlorobenzenes
- Chlorofluorocarbons (CFCs) and Hydrochlorofluorocarbons (HCFCs)
- Chloroprene (Neoprene)
- Chromium VI
- Chlorinated Polyvinyl Chloride (CPVC)
- Formaldehyde (added)
- Halogenated Flame Retardants (HFRs)
- Lead (added)
- Mercury
- Polychlorinated Biphenyls (PCBs)
- Perfluorinated Compounds (PFCs)
- Phthalates
- Polyvinyl Chloride (PVC)
- Polyvinylidene Chloride (PVDC)
- Short Chain Chlorinated Paraffins
- Wood treatments containing Creosote, Arsenic or Pentachlorophenol
- Volatile Organic Compounds (VOCs) in wet applied products[\*]

[\*] Wet applied products (coating, adhesives and sealants) must have VOC levels below the South Coast Air Quality Management District (SCAQMD) RULE 1168 for Adhesives and Sealants or the Carbon 2007 Suggested Control Measure (SCM) for Architectural Coatings as applicable. Containers of sealants and adhesives with capacity of 16 ounces or less must comply with applicable limits in the California Air Resources Board (CARB) Regulation for Reducing Emissions from Consumer products.

JR Anderson  
President  
Acoustical Surfaces, Inc.