



Acoustical Surfaces, Inc.

SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318
(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: sales@acousticalsurfaces.com
Visit our Website: www.acousticalsurfaces.com

We Identify and **S.T.O.P.** Your Noise Problems

NOISE S.T.O.P.™ Contact Adhesive Spray

Heavy Duty Wide Web Spray Adhesive

- Wide Web Spray
- Temporary or Permanent Bond to Most Surfaces
- No Chlorinated Solvents
- No Ozone Depleters
- Waterproof, Flexible, Transparent and Non-Staining
- Ideal for Uneven or Porous Surfaces or Weight Materials
- Use This Product for Your Toughest Adhesive Applications



MATERIAL: Professional spray adhesive.

FEATURES: Very aggressive.

SIZE: 12 oz.

APPLICATIONS: Foam, wood, cardboard, paper, metal, cloth, plastic, fabrics, canvas, carpet, foils, photos, felt, leather, rubber, cork, glass, films, fiberglass, tissue paper, collages, ceramics, balsa wood, styrofoam, displays, photocomposition, layouts, trims, jute pads, kick pads, latex foams, polyurethane foams, styrene board, drywall, particle board, laminate, insulation, polyethylene film, PVC drywall trim, HVAC duct liner.

FLAMMABILITY: Flammable. **V.O.C. CONTENT:** 54.9%.

HMIS RATING: Health = 2, Flammability = 3, Reactivity = 0, Personal Protection = B.


DIRECTIONS: Always shake well before using. Never aim valve at face. Hold can upright and apply adhesive in a side-to-side motion 10 to 14 inches from surface. **TEMPORARY BONDS:** Spray one surface, allow to tack, then apply material to be bonded. **PERMANENT BONDS:** Liberally spray both surface and material, allow to tack, then apply. **CLEANING SPRAY TIP:** When finished with a particular spray application, always turn can upside down and spray for two seconds to clear valve and prevent clogging. If adhesive accumulates around nozzle, wipe clear while wet. If dried in valve opening, remove with degreasing solvent.

DANGER: Contains Acetone and Hexane. Extremely Flammable. Use with adequate ventilation. Keep away from heat, sparks, open flame or other ignition sources. Harmful or fatal if swallowed. Do not take internally. If swallowed, do not induce vomiting. Contact a physician immediately. Vapor harmful. Avoid inhalation of spray mist or vapors. If overcome, move patient to fresh air. Call a physician immediately. Eye irritant. Avoid contact with eyes and skin. In case of eye contact, flush immediately with water and continue for 15 minutes. If irritation persists, see a physician. For skin contact, wash with soap and water. If irritation persists, call a physician immediately. Contents under pressure. Do not puncture or incinerate container. Do not store at temperatures above 120°F. **KEEP OUT OF REACH OF CHILDREN.**

CAS NUMBERS: Isobutane/Propane Blend.

Installation Recommendations

Wall installations:
1/4" perimeter bead w/X
and spots of
Professional Wide Web
Spray Adhesive
on both wall and
panel.



Note: 2 cans of Professional Wide Web Spray Adhesive and 4 tubes of PSA-29 Acoustical Panel Adhesive are needed for 16 - 2' x 4' panels.